

PopUp Gooseneck Hitch

We are located in and ship from the central United States. We are an authorized PopUp Hitch dealer. All of our products are Brand New current models, unless clearly indicated. We ship the same or next business day via UPS ground. If by chance your ordered item is not in stock, we will email, and or phone you to let you know.

Electric hydraulic Trailer Jack landing gear. Designed with rugged tube-in-tube construction. Never crank that trailer jack again.

Blue Ox SwayPro Weight Distribution & Sway Control Hitches

Blue Ox Towing products for towing vehicles:

Blue Ox Towing products for towing vehicles:

Blue Ox TigerTrak Stabilizer bars:

PopUp Flip Over Gooseneck Hitch



Flip-Over Gooseneck Hitches: 2-5/16" ball, 30,000 pounds gross trailer weight. Flip-Over the ball for a level bed; the ball can rotate in the socket to keep it clean and save the ball from a bad coupler; rotate the handle 90 degrees to release the ball or lock it.

You do not have to try to hook or catch a small handle to release or lock the ball and there are no corners from a square gooseneck hitch ball to collect dirt that can freeze the ball in the socket.

PopUp goosneck hitch, all bolt together using existing holes, and installs without loosening or removing the bed. PopUp gooseneck hitches are designed Vehicle specific for a perfect fit and easy installation.

Complete hitch including 2-5/16" ball, all hardware and easy read instructions.

Retractable Gooseneck Hitch



Popup2 Retractable Gooseneck Hitch, pull the lever and raise the gooseneck hitch ball for a secure latched position, push the lever to lower the gooseneck ball for a level pickup bed. A time proven, heavy duty 30,000 pound rated gooseneck hitch.

Gooseneck Hitch for Semi-Tractor



Use your Semi-Tractor to tow gooseneck trailers (class 6, 7, & 8 tractors). The Flip-Over Semi-tractor gooseneck hitch by PopUp Towing Products is for class 6,7 & 8 Semi-Tractors. These truck frames are 34" across (the hitch normally runs 34-3/16" to 34-1/4" more than enough to work on 34" frames. The hitch sits behind the 5th wheel hitch, over the frame, using 10" on top and 4" down the side of the frame.

Contact Us

Popup Gooseneck Hitch

PO Box 184,

Shell Knob, MO 65747

417-858-0537

Email: info@hitchescouplers.com

<http://www.popupgooseneckhitch.com>